




BLA ETECH PVT. LTD.


EMC, EMI FILTER & POWER SOLUTION

Single Phase Filter BLPCB02-XX-X

General Purpose Entry Module EMI Filter



CIRCUIT DIAGRAM:



Technical Specification

Max Rated Voltage 250VAC

Operating Frequency 50/60Hz

Rated Current 1A to 10A @40°C

Hipot Test Voltage-

L-L 1450 VDC 2sec

L-G 2250 VDC 2sec

Temperature Range -25 to +85°C(25/85/21)

- Rated currents from 1 to 10A
- Single stage filter
- High differential mode attenuation

Applications:

- Industrial Equipment Vulnerable to Transients on the AC Power Line (Computers, Traffic Controls, Etc.)
- Communications systems and other industrial systems,
- Protection of Equipment Connected to Telephone or Signal Lines, Such as Security Systems, Railroad Equipment, Fire Alarm Systems, Etc
- For the purpose of protecting against electrical surges and spikes, including those caused by lightning.
- Arc Suppression Across Relay and Switch Contacts
- Scaled-down versions of these devices are sometimes installed in residential service entrance electrical panels, to protect equipment in a household from similar hazards

Features:

- Nanosecond Switching Response Time, <15 ns, with Minimal Lead Length.
- Various noisy applications requires high performance filter.
- No Extinguishing or Follow-On Current Limitations.


Benefits:

- Eliminates Dangerous Voltage Transients.
- Lowers Overall System Costs by Reducing Downtime and Maintenance Costs.
- Improves Component and System Reliability.
- Reduces EMP/RFI Interference.

FILTERS SELECTION TABLE

SN	PART NO	RATED CURRENT @40°C A	LEAKAGE CURRENT 250V/50Hz mA	MECHANICAL DIMENSION L X W X H (mm)	CONNECTION TYPE
1	BLPCB02-01-H	1	0.8	41 X 31 X 20	HOLE MOUNTING
2	BLPCB02-03-H	3	0.8	41 X 31 X 20	HOLE MOUNTING
3	BLPCB02-06-H	6	0.8	41 X 31 X 20	HOLE MOUNTING
4	BLPCB02-10-H	10	0.8	41 X 31 X 20	HOLE MOUNTING

MECHANICAL DETAIL



REMARK

All dimension are in mm

INSERTION LOSS(dB)

1A

MHZ	0.5	1	2	5	10
CM	32	35	37	41	42
DM	19	23	33	44	45

3A

MHZ	0.5	1	2	5	10
CM	27	33	39	41	43
DM	17	21	35	44	44

6A

MHZ	0.5	1	2	5	10
CM	22	26	31	39	43
DM	16	21	31	38	42

10A

MHZ	0.5	1	2	5	10
CM	15	19	28	33	39
DM	14	18	27	34	42

CORPORATE OFFICE AND MANUFACTURING UNIT

**BLA ETECH PVT LTD
A-42
WAZIRPUR INDUSTRIAL AREA
NEW DELHI-110052
INDIA**



CONTACT DETAIL

WEB- www.blaetech.com

Email- info@blaetech.com

TEL- +91-11-47483290

Mob-+91-9899197050